

DUPLEX STEEL

UNS S20910 - 1.3964



UNS S20910 - 1.3964

Duplex steel 1.3964 is a stainless steel that has high strength and corrosion resistance. It is also known as Nitronic 50, XM-19, or 1.396412 and contains more chromium, nickel, molybdenum, and nitrogen than regular stainless steels, which gives it better resistance to pitting, crevice corrosion, and stress corrosion cracking.

KEY FEATURES

- Good mechanical properties
- High corrosion resistance in coastal environments
- Moderately low thermal conductivity

CHEMICAL PROPERTIES

Chromium (Cr)	Nickel (Ni)	Manganese (Mn)	Molybdenum (Mo)	Silicone (Si)	Copper (Cu)	Carbon (C)	Nitrogen (N)	Vanadium (V)	Niobium (Nb)	Phosphorus (P)	Sulphur (S)
20-22%	11.5-13.5%	4-6%	3-3.5%	1%	0.5-1%	0.03%	0.25%	0.2%	0.2%	0.025%	0.01%

MECHANICAL PROPERTIES

Tensile strength (N/mm ²)	700-950
Yield strength (N/mm ²)	370
Elongation (% in 4D)	35
Hardness - Rockwell (HRB) max	110
Hardness - Brinell (HB) max	293

PHYSICAL PROPERTIES

Density (kg/m ³)	7900	
Modulus of elasticity (Gpa)	195	
Mean coefficient of thermal expansion	0-100°C (µm/m/°C)	15.7
	0-350°C (µm/m/°C)	17.2
	0-538°C (µm/m/°C)	18.0
Thermal conductivity	at 100°C (W/m.K)	14.0
	at 500°C (W/m.K)	19.3
Specific Heat 0-100°C (J/kg.K)	460	
Electrical resistivity (nΩ.m)	810	
Melting point (°C)	1450	

MARKET SECTORS



Engineering Components
Springs, bolts, fasteners



Chemical Processing
Pumps, valves, components



Marine Equipment
Boat shafts, propellers, fasteners



Power Generation
Components in power plants, turbine blades, shafts



Oil & Gas Industry
Valves, fittings, downhole equipment



Aerospace Industry
Fittings, fasteners, structural elements